Page 2

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

LISTING OF CLAIMS:

- 1. (Original) A method for forming a non-woven fibrous web comprised of aramid fibers, and aramid fibrid, which comprises:
- (i) forming a foam furnish by agitating aramid fibers in a foamed medium, the furnish also containing aramid fibrid, with an apparatus comprising agitating means mounted for displacement within the foamed medium and including a leading surface facing in a direction of displacement, the leading surface including upper and lower portions converging in the direction of displacement to form a generally convex leading surface; and driving means for displacing the agitating means in the direction of displacement for dispersing and mutually separating the fibers within the foamed medium; and
- (ii) passing the foam furnish onto a screen and defoaming the furnish to form the web.
- 2. (Original) The method of claim 1, wherein the aramid fibers agitated are comprised of fibers at least one-half inch in length.
- 3. (Original) The method of claim 1, wherein the fibers agitated are further comprised of cellulosic fibers.

- 4. (Original) The method of claim 1, wherein the fibers agitated are further comprised of synthetic and/or metal fibers.
- 5. (Original) The method of claim 1, wherein the fibers agitated comprise inorganic fibers.
- 6. (Original) The method of claim 1, wherein the agitation in step (i) creates a foam furnish having an air content of at least 50% by volume.
- 7. (Original) The method of claim 1, wherein the air content of the foam furnish is at least 75% by volume.
- 8. (Original) The method of claim 1, wherein the weight percent solids of the foam furnish passed onto the wire screen is in the range of from 0.2 to 2.0.
- 9. (Original) The method of claim 1, wherein the weight percent solids of the foam furnish is greater than 0.5.
- 10. (Original) The method of claim 1, wherein the foamed medium is formed during the agitation of the fibers.
- 11. (Original) The method of claim 1, wherein the foamed medium is formed prior to agitation of the aramid fibers.

- 12. (Original) The method of claim 1, wherein the ratio of agitator width to aramid fiber length is at least 1.25.
- 13. (Original) The method of claim 1, wherein the ratio of agitator width to aramid fiber length is at least 1.75.
- 14. (Original) The method of claim 1, wherein the ratio of agitator width to aramid fiber length is at least 3.0.
- 15. (Original) The method of claim 2, wherein the aramid fibers are comprised of fibers at least one inch in length.
- 16. (Original) The method of claim 2, wherein the aramid fibers are comprised of fibers at least one and one-half inch in length.
- 17. (Original) The method of claim 1, wherein the leading surface of the agitating means terminates in upper and lower trailing ends.
- 18. (Original) The method of claim 1, wherein the agitating means includes a non-convex trailing surface facing away from the direction of displacement.
- 19. (Original) The method of claim 1, wherein the trailing surface is generally concave.

- 20. (Original) The method of claim 1, wherein the leading surface of the agitating means is continuously curved.
- 21. (Original) The method of claim 1, wherein the leading surface of the agitating means comprises a hollow cylinder.

Claims 22-26 (Cancelled).